Visual-signal Appliances for Fire-protective Signaling Systems

COMPANY
Simplex Time Recorder Co
6 TECHNOLOGY PARK DR
WESTFORD, MA 01886 United States

S3079

Strobe lights, 1 Hz, non-addressable, synchronizable, Models *4906-9107* (White Housing), *4906-9108* (Red Housing), having selectable candela ratings of 15, 30, 75 and 110 cd. Available in amber lens only. Intended for indoor use, wall-mounting only.

Strobe lights, 1Hz, True Alert Non-Addressable, (synchronizable), Models *4906-9105*+ (Red Housing), *4906-9106*+ (White Housing), having selectable candela settings of 15, 60, 75 and WP75. Wall-mounting only. Candela settings of 15, 60 and 75 are intended for indoor use only. The WP75 setting is a 75 candela rating intended for indoor or outdoor/damp use when used with a model *49WPBB-AVVOWR* or *49WPBB-AVVOWW* weatherproof backbox.

Horn/Strobes, 1Hz, Non-Addressable, (synchronizable), Models *4906-9131*+, *4906-6131*+ (Red Housing), *4906-9132*+ (White Housing), having selectable candela ratings of 15, 60, 75 and WP75. Wall-mounting only. Candela settings of 15, 60 and 75 are intended for indoor use only. The WP75 setting is a 75 candela rating intended for indoor or outdoor/damp use when used with a model *49WPBB-AVVOWR* or *49WPBB-AVVOWW* weatherproof backbox.

Models *4906-9137*, *4906-9138*. Multi-candela, selectable to 15, 30, 75, 110 cd. Intended for wall mounting only. Intended for indoor use only. Intended for use with either Models *4009-9201*, *4009-9301* IDNet NAC Extender or with *4905-9938* SmartSync Control Module (SCM) or with 4100U and 4010 Fire Alarm Control Panel (FACPs).

Strobe lights, 1Hz, TrueAlert Addressable (synchronizable), Models *4906-9205 (Red Housing, Amber lens)*, *4906-9206 (White housing, Amber lens)*, *4906-9209 (Red Housing, Blue lens)*. Multi-candela, selectable to 15, 30, 75, 110 cd. Intended for indoor use, wall-mounting only. Intended for use with either Model *4009-9401* NAC Extender or with the TrueAlert Power Supply of Model *4100U FACP or EPS*.

Strobe lights, 1Hz, TrueAlert Addressable (synchronizable), Model *4906-9207 (Amber lens)* and *4906-9210 (Blue lens)*. Multi-candela, selectable to 15, 30, 75, 110 cd. Intended for use with either Model *4009-9401* NAC Extender or with the TrueAlert Power Supply of Model *4100U FACP or EPS*.

Chime/Strobes, Models *4906-9133*, *4906-9134* Multi-candela, selectable to 15, 30, 75, 110 cd. Intended for wall mounting only. Intended for indoor use only. Intended for use with either Models *4009-9201*, *4009-9301* IDNet NAC Extender or with *4905-9938* SmartSync Control Module (SCM) or with 4100U and 4010 Fire Alarm Control Panel (FACPs). Intended for private mode use only.

Models *4906-9135*, *4906-9136* Multi-candela, selectable to 15, 30, 75, 110 cd. Intended for ceiling mounting only. Intended for indoor use only. Intended for use with either Models *4009-9201*, *4009-9301* IDNet NAC Extender or with *4905-9938* SmartSync Control Module (SCM) or with *4100U* and *4010* Fire Alarm Control Panel (FACPs). Intended for private mode use only.

Complete strobes, True Alert ES Addressable, Models *49VO-WRA-A*, *49VO-WRA-A-BA*, *49VO-WWA-A*, *49VO-WWA-A-BA*, *49VO-WWS-A-BA*. Intended for indoor use, wall mounting only. Only available with amber lens.

Main Body only, True Alert ES Addressable, Model *49VO-APPLWE*, *49VO-APPLWE-BA*. Intended for indoor use. Available with amber lens (model *49LENS-AMBER*), blue lens (model *49LENS-BLUE*), green lens (model *49LENS-GREEN*) and red lens (model *49LENS-RED*). To be used with models *49VO-WRA-A*, *49VO-WRA-A-BA*, *49VO-WWA-A*, *49VO-WWA-A-BA*, *49VO-WWS-A-BA*.

Lens Covers, Models *49LENS-AMBER (amber color)*; *49LENS-BLUE (blue color)*; *49LENS-GREEN (green color)*; *49LENS-RED (red color)*.

Weatherproof backbox, Models *49WPBB-AVVOWR* and *49WPBB-AVVOWW*.

+ For connection to Listed control units or sync modules with which compatibility was determined by test or a review of circuit parameters. Interconnection and compatible models indicated on installation wiring diagram for visual signaling appliance, control unit, and/or sync module.

Last Updated on 2021-12-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."