TrueAlert Non-Addressable Multi-Tone Horns and Chimes

Wall-Mounted



Non-Addressable Chime/Strobe

TrueAlert multi-candela chime/strobe provides private mode audible notification for applications requiring notification of trained personnel instead of the general public. Typical applications would be in medical patient areas where the softer chime tones are less disruptive than conventional fire alarm audible notification.

Datasheet: S4906-0012

Product	Part Number	Description
Appliance (complete)	4906-9133	Non-Addressable Chime/Strobe, 15/30/75/110/135/185cd, SmartSYNC, Red, "FIRE"
	4906-9134	Non-Addressable Chime/Strobe, 15/30/75/110/135/185cd, SmartSYNC, White, "FIRE"
Accessory	2975-9145	Mounting Box, Red (requires 4905-9931 Adapter Plate)
	4905-9931	Adapter Plate, Red for mounting to Simplex 2975-9145 Box (typically for retrofit, mount vertical or horizontal)
	4905-9937	Adapter Skirt, Surface-Mount, Red
	4905-9938	SmartSync Control Module
	4905-9940	Adapter Skirt, Surface-Mount, White
	4905-9961	Wire guard, Red with mounting plate, compatible with semiflush-mounting or surface mount boxes

TrueAlert Non-Addressable Multi-Tone Horns and Chimes

Ceiling-Mounted



Non-Addressable Chime/Strobe

TrueAlert multi-candela chime/strobe provides private mode audible notification for applications requiring notification of trained personnel instead of the general public. Typical applications would be in medical patient areas where the softer chime tones are less disruptive than conventional fire alarm audible notification.

Datasheet: S4906-0012

Product	Part Number	Description
Appliance (complete)	4906-9135	Non-Addressable Chime/Strobe, 15/30/75/110/135/185cd, SmartSYNC, Red, "FIRE"
	4906-9136	Non-Addressable Chime/Strobe, 15/30/75/110/135/185cd, SmartSYNC, White, "FIRE"
Accessory	4905-9915	Adapter Skirt, White for mounting to 1 1/2 inch deep electrical box
	4905-9916	Adapter Skirt, Red for mounting to 1 1/2 inch deep electrical box
	4905-9927	Wire Guard, Red, Semi-Flush Mounting (requires 4905-9928 mounting plate for 4905-9923, -9924, and -9145 boxes)
	4905-9938	SmartSync Control Module

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Wall-Mounted



Non-Addressable Speaker

4902 Series speakers provide high-quality sound for emergency fire alarm use as well as for background music. The moisture-repellent speaker is designed for smooth frequency response with minimal distortion.

Datasheet: S4902-0003

Product	Part Number	Description
Appliance (complete)	4902-9716	TrueAlert Speaker, Wall-Mount, 25/70.7V, 1/4, 1/2, 1, 2watts, Red, "FIRE"
	4902-9717	TrueAlert Speaker, Wall-Mount, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
Accessory	2975-9145	Mounting Box, Red (requires 4905-9931 Adapter Plate)
	4905-9931	Adapter Plate, Red for mounting to Simplex 2975-9145 Box (typically for retrofit, mount vertical or horizontal)
	4905-9941	Adapter Skirt, Surface-Mount, Red
	4905-9942	Adapter Skirt, Surface-Mount, White

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Wall-Mounted



Non-Addressable Speaker/Strobe

The TrueAlert multi-candela speaker and synchronized strobe provides convenient installation to standard electrical boxes with extensions. The enclosure designs are both impact and vandal resistant and provide a convenient strobe intensity selection. Since each model can be selected for strobe intensity output, onsite model inventory is minimized and changes encountered during construction can be easily accommodated. Wall mount S/V housings are a one-piece assembly (including lens) that mounts to a four-inch square electrical box with extension.

Datasheet: S4906-0003

Product	Part Number	Description
Appliance (complete)	4906-9151	TrueAlert Multi-Candela Speaker/Strobe, Wall-Mount, UL/ULC, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, Red, "FIRE"
	4906-9153	TrueAlert Multi-Candela Speaker/Strobe, Wall-Mount, UL/ULC, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
Cover	4905-9996	Cover, Red, "FIRE"
	4905-9845	Cover, Red, "ALERT"
	4905-9811	Cover, Red, Blank
	4905-9997	Cover, White, "FIRE"
	4905-9846	Cover, White, "ALERT"
	4905-9991	Cover, White, Logo Only
	4905-9812	Cover, White, Blank
Accessory	2975-9145	Mounting Box, Red (requires 4905-9903 Adapter Plate)
	4905-9903	Adapter Plate for mounting to 2975-9145 back box
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9938	SmartSync Control Module
	4905-9946	Adapter Skirt, Red for mounting to 1 1/2 inch deep electrical box
	4905-9947	Adapter Skirt, White for mounting to 1 1/2 inch deep electrical box
	4905-9998	Wire guard, Red with mounting plate, compatible with semiflush or surface mount boxes

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Wall-Mounted



Non-Addressable Speaker/Strobe, Fixed-Candela

TrueAlert non-addressable speaker/visible (S/V) notification appliances combine a multi-tapped speaker and a high-intensity strobe to provide audio/tone notification and visible notification from the same appliance. Speakers and strobes are wired separately. The speaker is multi-tapped with taps available for either 25 VRMS or 70.7 VRMS and the strobe is selectable for either free-run or synchronized operation.

Datasheet: S4903-0015

Product	Part Number	Description
Appliance (complete)	4903-9356	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 15cd, 2-Wire, Free-Run/Sync, Red, "FIRE"
	4903-9357	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 75cd, 2-Wire, Free-Run/Sync, Red, "FIRE"
	4903-9358	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 110cd, 2-Wire, Free-Run/Sync, Red, "FIRE"
	4903-9359	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 15cd, 2-Wire, Free-Run/Sync, White, "FIRE"
	4903-9360	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 75cd, 2-Wire, Free-Run/Sync, White, "FIRE"
	4903-9361	TrueAlert Non-Addressable Fixed-Candela Speaker/Strobe, Wall-Mount, 110cd, 2-Wire, Free-Run/Sync, White, "FIRE"
Cover	4905-9996	Cover, Red, "FIRE"
	4905-9997	Cover, White, "FIRE"
Accessory	2975-9145	Mounting Box, Red (requires 4905-9903 Adapter Plate)
	4905-9903	Adapter Plate for mounting to 2975-9145 back box
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9946	Adapter Skirt, Red for mounting to 1 1/2 inch deep electrical box
	4905-9947	Adapter Skirt, White for mounting to 1 1/2 inch deep electrical box
	4905-9998	Wire guard, Red with mounting plate, compatible with semiflush or surface mount boxes

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Ceiling-Mounted



Non-Addressable Speaker

4902 Series speakers provide high-quality sound for emergency fire alarm use as well as for background music. The moisture-repellent speaker is designed for smooth frequency response with minimal distortion. Round speakers are available in off-white (no lettering).

Datasheet: S4902-0003

Product	Part Number	Description
Appliance (complete)	4902-9721	TrueAlert Speaker, Ceiling-Mount, 25/70.7V, 1/4, 1/2, 1, 2watts, White, “FIRE”
Accessory	2905-9946	Tile Bridge, Suspended Ceiling 2ft by 4ft tile size installation

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Ceiling-Mounted



Non-Addressable Speaker/Strobe

Multi-Candela TrueAlert S/Vs with speaker and synchronized strobe provides convenient installation to standard electrical boxes with extensions. The enclosure designs are both impact and vandal resistant and provide a convenient strobe intensity selection. Since each model can be selected for strobe intensity output, onsite model inventory is minimized and changes encountered during construction can be easily accommodated. Ceiling mount S/Vs also install using four-inch electrical boxes with an extension.

Datasheet: S4906-0003

Product	Part Number	Description
Appliance (complete)	4906-9154	TrueAlert Multi-Candela Speaker/Strobe, Ceiling-Mount, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
	4906-9157	TrueAlert Multi-Candela Speaker/Strobe, Ceiling-Mount, ULC, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
	4906-9158	TrueAlert Multi-Candela Speaker/Strobe, Ceiling-Mount, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "ALERT"
	4906-9159	TrueAlert Multi-Candela Speaker/Strobe, Ceiling-Mount, 15/30/75/110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, Blank
Accessory	2905-9946	Tile Bridge, Suspended Ceiling 2ft by 4ft tile size installation
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9938	SmartSync Control Module

TrueAlert Non-Addressable Speakers and Speaker/Strobes

Ceiling-Mounted



Non-Addressable Speaker/Strobe, Fixed-Candela

TrueAlert non-addressable Speaker/Visible (S/V) notification appliances combine a multi-tapped speaker and a high-intensity strobe to provide audio/tone notification and visible notification from the same appliance. Speakers and strobes are wired separately. The speaker is multi-tapped with taps available for either 25 VRMS or 70.7 VRMS and the strobe is selectable for either free-run or synchronized operation.

Datasheet: S4903-0019

Product	Part Number	Description
Accessory	4903-9196	TrueAlert Non-Addressable Speaker/Strobe, Round, Ceiling-Mount, 15cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
	4903-9197	TrueAlert Non-Addressable Speaker/Strobe, Round, Ceiling-Mount, 30cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
	4903-9198	TrueAlert Non-Addressable Speaker/Strobe, Round, Ceiling-Mount, 110cd, 25/70.7V, 1/4, 1/2, 1, 2watts, White, "FIRE"
	2905-9946	Tile Bridge, Suspended Ceiling 2ft by 4ft tile size installation
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps

TrueAlert Non-Addressable Module

SmartSync Adapter Module

Standard SmartSync operation notification appliances activate horns and/or strobes in response to commands received from the SmartSync operation control source using a two-wire connection.

Datasheet: S4905-0005

Product	Part Number	Description
Module	4905-9815	SmartSync Adapter Module, mounts in 4-11/16" (119mm) square, 2" (51mm) minimum depth electrical box, requires surface or flush mount cover plate
Accessory	4081-9008	End-of-Line Resistor Harness (ref. 733-894); 10 kΩ, ½ W; two required, one each for audible and visible output
	4905-9817	Cover Plate, Surface Mount, Beige
	4905-9818	Cover Plate, Flush Mount, Beige

Conventional Notification - Horns, Strobes and Horn/Strobes

Wall-Mounted





Visible Notification Appliance, Fixed Candela

4904 Series wall-mounted visible notification appliances provide symmetrical light output in key axis directions by utilizing a compound, multi-surface reflector. The lens assembly fits securely into its housing, providing a high-integrity notification appliance that is impact and vandal resistant and suitable for a variety of applications. Wall Mount Strobes are available in red or white for vertical mounting and in red for horizontal mounting.

Datasheet: S4904-0008

Product	Part Number	Description
Appliance (complete)	4904-9174	Visible Notification Appliance, Wall-Mount, 30cd, Free-Run/Sync, Red, "FIRE" and Logo (vertical mount)
	4904-9175	Visible Notification Appliance, Wall-Mount, 110cd, Free-Run/Sync, Red, "FIRE" and Logo (vertical mount)
	4904-9176	Visible Notification Appliance, Wall-Mount, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (vertical mount)
	4904-9177	Visible Notification Appliance, Wall-Mount, 15cd, Free-Run/Sync, White, "FIRE" and Logo (vertical mount)
	4904-9178	Visible Notification Appliance, Wall-Mount, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
Accessory	4905-9910	Adapter Plate for mounting to Wiremold Box or handy electrical box (typically surface applications)
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9926	Wire guard, Red with mounting plate, compatible with semiflush or surface mount boxes
	4905-9938	SmartSync Control Module

Conventional Notification - Horns, Strobes and Horn/Strobes

Wall-Mounted



Audible/Visible Notification Appliance, Fixed Candela

Audio/Visible (A/V) notification appliances combine a high-intensity strobe with a low-current electronic horn. The horn output provides a steady, harmonically rich sound that can be easily coded by the controlling notification appliance circuit (NAC). A/V notification appliances with electronic horns are available for horizontal or vertical mounting.

Datasheet: S4903-0017

Product	Part Number	Description
Appliance (complete)	4903-9252	Audio/Visible Notification Appliance, Wall-Mount, 4-Wire, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9253	Audio/Visible Notification Appliance, Wall-Mount, 4-Wire, 30cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9254	Audio/Visible Notification Appliance, Wall-Mount, 4-Wire, 110cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9255	Audio/Visible Notification Appliance, Wall-Mount, 4-Wire, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (vertical mount)
Accessory	2975-9145	Mounting Box, Red (requires 4905-9903 Adapter Plate)
	4905-9903	Adapter Plate for mounting to 2975-9145 back box
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9916	Adapter Skirt, Red for mounting to 1 1/2 inch deep electrical box
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9923	Surface Mount Box, Red
	4905-9927	Wire Guard, Red, Semi-Flush Mounting (requires 4905-9928 mounting plate for 4905-9923, -9924, and -9145 boxes)
	4905-9931	Adapter Plate, Red for mounting to Simplex 2975-9145 Box (typically for retrofit, mount vertical or horizontal)
	4905-9939	Adapter Plate for mounting to Wiremold Box or 2 gang electrical box (typically retrofit applications)

Conventional Notification - Horns, Strobes and Horn/Strobes

Ceiling-Mounted



Visible Notification Appliance, Fixed Candela

4904 Series ceiling-mounted visible notification appliances provide symmetrical light output in key axis directions by utilizing a compound, multi-surface reflector design. The lens assembly fits securely into its housing, providing a high-integrity notification appliance that is impact and vandal resistant and suitable for a variety of applications. Ceiling-mount strobes are available in red with white lettering and white without lettering.

Datasheet: S4904-0009

Product	Part Number	Description
Appliance (complete)	4904-9183	Visible Notification Appliance, Ceiling-Mount, 15cd, 24V, Free-Run/Sync, Red, "Fire"
	4904-9184	Visible Notification Appliance, Ceiling-Mount, 30cd, 24V, Free-Run/Sync, Red, "Fire"
	4904-9185	Visible Notification Appliance, Ceiling-Mount, 110cd, 24V, Free-Run/Sync, Red, "Fire"
	4904-9345	Visible Notification Appliance, Ceiling-Mount, 15cd, 24V, Free-Run/Sync, White, Blank
	4904-9346	Visible Notification Appliance, Ceiling-Mount, 30cd, 24V, Free-Run/Sync, White, Blank
	4904-9360	Visible Notification Appliance, Ceiling-Mount, 75cd, 24V, Free-Run/Sync, White, Blank
Accessory	4905-9910	Adapter Plate for mounting to Wiremold Box or handy electrical box (typically surface applications)
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9926	Wire guard, Red with mounting plate, compatible with semiflush or surface mount boxes
	4905-9938	SmartSync Control Module

Conventional Notification - Speakers and Speaker/Strobes

Wall-Mounted



Speaker/Visible Notification Appliance, Fixed-Candela

Speaker/Visible (S/V) notification appliances combine a multi-tapped speaker and a high-intensity strobe to provide audio/tone notification and visible notification from the same appliance. Audible/Visible notification appliances with electronic horns are available for horizontal or vertical mounting.

Datasheet: S4903-0016

Product	Part Number	Description
Appliance (complete)	4903-9148	Speaker/Visible Notification Appliance, Wall-Mount, 4-Wire, 30cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9149	Speaker/Visible Notification Appliance, Wall-Mount, 4-Wire, 110cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9150	Speaker/Visible Notification Appliance, Wall-Mount, 4-Wire, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (horizontal mount)
	4903-9153	Speaker/Visible Notification Appliance, Wall-Mount, 4-Wire, 15cd, Free-Run/Sync, Red, "FIRE" and Logo (vertical mount)
	4903-9193	Speaker/Visible Notification Appliance, Wall-Mount, 4-Wire, 15cd, Free-Run/Sync, White, "FIRE" and Logo (vertical mount)
Accessory	2975-9145	Mounting Box, Red (requires 4905-9903 Adapter Plate)
	4905-9903	Adapter Plate for mounting to 2975-9145 back box
	4905-9914	Synchronized Flash Module (Class B), 2 amps
	4905-9915	Adapter Skirt, White for mounting to 1 1/2 inch deep electrical box
	4905-9916	Adapter Skirt, Red for mounting to 1 1/2 inch deep electrical box
	4905-9922	Synchronized Flash Module (Class A), 2 amps
	4905-9923	Surface Mount Box, Red
	4905-9927	Wire Guard, Red, Semi-Flush Mounting (requires 4905-9928 mounting plate for 4905-9923, -9924, and -9145 boxes)
	4905-9939	Adapter Plate for mounting to Wiremold Box or 2 gang electrical box (typically retrofit applications)

Visual Messaging



TrueAlert Text Messaging Appliance

High-visibility, multi-color LED text message board provides visible textual alarm notification controlled from compatible fire alarm control units. Up to 32 pre-programmed messages can be activated in response to pre-defined emergency situations.

Datasheet: J4907-0002

Product	Part Number	Description
Message Board	4907-9007	TrueAlert Messaging Appliance, Wall/Ceiling-Mounted, Dark Gray with optional VESA bracket mounting or for ceiling cable mounting
Accessory	4907-9002	Mounting Bracket, Wall-Mounted, Dark Gray, adjustable swivel
	4907-9003	Mounting Bracket, Wall-Mounted, Dark Gray, fixed
	4907-9005	Ethernet Cable, 15 feet length (connect for non-fire alarm messaging)
	4907-9006	Mounting Box, Wall-Mounted, Dark Gray

Hyperspike Encompass System



Encompass Amplifier Cabinets

Engineered and designed with the latest mass notification control technology. When paired with with a HyperSpike® MA -2 speaker, the Encompass Amplifier Cabinet is optimized to produce clear and authoritative voice commands with an acoustic footprint of greater than 12 square miles.

Datasheet: 90240A-SS

Product	Part Number	Description
Amplifier	90240A-801	Hyperspike Encompass MA-Micro Amplifier Cabinet, Universal-Mount, Gray
	90240A-802	Hyperspike Encompass MA-1 Amplifier Cabinet, Universal-Mount, 320watts, Gray
	90240A-803	Hyperspike Encompass MA-1 Amplifier Cabinet, Universal-Mount, 640watts, Gray
	90240A-804	Hyperspike Encompass MA-1 Amplifier Cabinet, Universal-Mount, 960watts, Gray
	90240A-805	Hyperspike Encompass MA-1 Amplifier Cabinet, Universal-Mount, 1600watts, Gray
	90240A-806	Hyperspike Encompass MA-2 Amplifier Cabinet, Universal-Mount, 1280watts, Gray
	90240A-807	Hyperspike Encompass MA-2 Amplifier Cabinet, Universal-Mount, 1920watts, Gray
	90240A-808	Hyperspike Encompass MA-2 Amplifier Cabinet, Universal-Mount, 3200watts, Gray
Accessory	72538B-801	Hyperspike Encompass Floor Pedestal Mount Kit, Gray
	72539B-801	Hyperspike Encompass Wall-Mount Kit, Gray
	72540B-801	Hyperspike Encompass Pole-Mount Kit, Gray
	72551B-801	25/70/100V Transformer Kit

Other Notification - Bells



Wheelock Motor Bell

The Wheelock MB motor bells provide a specifically designed motor bell for fire and life safety alarm systems. The Wheelock MB bells include higher dBA, low current draw, a built-in trimplate for semi-flush mounting, low-frequency aluminum shells, and low RFI noise. The motor for MB bells is a durable, high-torque permanent magnet motor selected for its high performance and long life.

Datasheet: TD450055EN

Product	Part Number	Description
Appliance (complete)	MB-G10-12-R	Wheelock Motor Bell, Wall-Mount, Weatherproof, 12VDC, 10 inch, Red, Blank
	MB-G6-12-R	Wheelock Motor Bell, Wall-Mount, Weatherproof, 12VDC, 6 inch, Red, Blank
	MB-G6-24-S	Wheelock Motor Bell, Wall-Mount, Weatherproof, 24VDC, 6 inch, Silver, Blank
Accessory	AP-R	Adapter Plate, Wall-Mount, Red
	AP-W	Adapter Plate, Wall-Mount, White
	BB-R	Backbox, Wall-Mount, 4 inch square (Steel), Red
	DBB-R	Backbox, Deep 4 inch square (Steel), Red
	DBB-W	Backbox, Deep 4 inch square (Steel), White
	RP-R	Adapter Plate (Retrofit), Wall-Mount, Red
	RP-W	Adapter Plate (Retrofit), Wall-Mount, White
	SBB-R	Backbox, Wall-Mount (Surface), Red
	SBB-W	Backbox, Wall-Mount (Surface), White
	SFP-R	Adapter Plate, Semi-Flush, Wall-Mount, Red
	SFP-W	Adapter Plate, Semi-Flush, Wall-Mount, White
	SHBB-R	Backbox, Wall-Mount, Surface, Red
	SHBB-W	Backbox, Wall-Mount, Surface, White
	WBB-R	Backbox, Weatherproof, Red
	WBB-R-3/4T-3/4B	Backbox, Weatherproof, 3/4 Threaded, Red
	WBB-W	Backbox, Weatherproof, White

Other Notification - Bells





Wheelock 43T AC Bells

The Wheelock 43T bells provide the durable operation and dependable performance required for life safety alarm systems. A complete range of vibrating models is offered in six inch and ten inch sizes for 115- or 24-volt AC operation in indoor or outdoor installations. All models provide high sound output with low power consumption.

Datasheet: TD450054EN

Product	Part Number	Description
Appliance (complete)	43T-G10-115-R	Wheelock 43T Bell, 10", 115VAC, Red
	43T-G10-115-S	Wheelock 43T Bell, 10", 115VAC, Sand
	43T-G10-24-R	Wheelock 43T Bell, 10", 24VAC, Red
	43T-G6-115-R	Wheelock 43T Bell, 6", 115VAC, Red
	43T-G6-115-S	Wheelock 43T Bell, 6", 115VAC, Sand
	43T-G6-24-R	Wheelock 43T Bell, 6", 24VAC, Red
Accessory	AP-R	Adapter Plate, Wall-Mount, Red
	AP-W	Adapter Plate, Wall-Mount, White
	RP-R	Adapter Plate (Retrofit), Wall-Mount, Red
	RP-W	Adapter Plate (Retrofit), Wall-Mount, White
	SFP-R	Adapter Plate, Semi-Flush, Wall-Mount, Red
	SFP-W	Adapter Plate, Semi-Flush, Wall-Mount, White
Backbox	DBB-R	Backbox, Deep 4 inch square (Steel), Red
	BB-R	Backbox, Wall-Mount, 4 inch square (Steel), Red
	SBB-R	Backbox, Wall-Mount (Surface), Red
	SHBB-R	Backbox, Wall-Mount, Surface, Red
	WBB-R	Backbox, Weatherproof, Red
	WBB-R-3/4T-3/4B	Backbox, Weatherproof, 3/4 Threaded, Red
	DBB-W	Backbox, Deep 4 inch square (Steel), White
	SBB-W	Backbox, Wall-Mount (Surface), White
	SHBB-W	Backbox, Wall-Mount, Surface, White
	WBB-W	Backbox, Weatherproof, White

Other Notification - Bells




Wheelock Series CVX/CSX Explosion-Proof Bell

The Wheelock Series CVX/CSX Explosion-Proof Bell is listed for service in Division One applications. Available in single-stroke and vibrating models with 24 VDC and 115 VAC versions. High sound output is provided through a large ten-inch bell shell. Outdoor models include protective hood and guard.

Datasheet: S0200 CVX/CSX

Product	Part Number	Description
Appliance (complete)	CSX10-24-R	Wheelock Series CVX/CSX Explosion-Proof Bell, Wall-Mounted, Red (refer to datasheet for hazardous classifications)
	CSX10-24-S	Wheelock Series CVX/CSX Explosion-Proof Bell, Wall-Mounted, Silver (refer to datasheet for hazardous classifications)

Other Notification - Beacons



Wheelock MAX Strobe

The Wheelock MAX Strobes are high-intensity, weather-resistant visible warning signals designed for stationary or mobile applications. Available in AC or DC voltage and with a steady-light option.

Datasheet: TD450098EN

Product	Part Number	Description
Appliance (complete)	AC-MAX-R	Wheelock MAX Strobe, 20cd, Double Flash, 120VAC, Red Lens
Appliance (complete)	DC-MAX-A	Wheelock DC-MAX Strobe, Various-Mounted, 24VDC, non-synch, 80cd, Amber Lens
	DC-MAX-C	Wheelock DC-MAX Strobe, Various-Mounted, 24VDC, non-synch, 100cd, Clear Lens
	DC-MAX-R	Wheelock DC-MAX Strobe, Various-Mounted, 24VDC, non-synch, 20cd, Red Lens
	DC-MAXS-R	Wheelock DC-MAX Strobe, Various-Mounted, 24VDC, non-synch, 20cd, Red Lens with 2 steady lights

Other Notification - Horns and Strobes



Wall-Mounted Wheelock MIZ Minihorn

Wheelock MIZ piezoelectric mini horns are compact electronic alarm appliances that are listed under UL Standard 464 for Audible Appliances in Public Mode Fire Protection Systems.

Datasheet: TD450052EN

Product	Part Number	Description
Appliance (complete)	MIZ-24S-R	Wheelock MIZ Minihorn, Wall-Mount, 24VDC, Red, Blank
	MIZ-24S-W	Wheelock MIZ Minihorn, Wall-Mount, 24VDC, White, Blank

Other Notification - Speakers and Speakers/Strobes



Wheelock S8 Speakers and Speaker/Strobes

The Wheelock S product line includes Speakers and Speaker Strobes are designed for high-efficiency sound output, with dual-voltage (25/70 VRMS) capability and field-selectable taps from 1/8 to eight watts.

Datasheet: TD450020EN

Product	Part Number	Description
Appliance (complete)	S8-70/25	Wheelock S8 Speaker, Ceiling-Mount, 8", 8watts, White, Blank
Accessory	CBB-8	Speaker Backbox, Ceiling-Mount, Black
	SSB-8	Speaker Support Bridge, Ceiling-Mount, 8 inch speaker
Appliance (complete)	S8-24MCC-FW	Wheelock S8 Speaker/Strobe, Ceiling-Mount, 8", 8watts, 15/30/75/95cd, White, "FIRE"
Accessory	CBB-8	Speaker Backbox, Ceiling-Mount, Black
	SSB-8	Speaker Support Bridge, Ceiling-Mount, 8 inch speaker

Other Notification - Speakers and Speakers/Strobes



Wheelock Vandal Resistant Speakers and Speaker/Strobes

The Wheelock ET Vandal Resistant speakers and speaker strobes provide a full range of rugged, high-performance combinations specifically designed to meet the critical needs of the life safety industry for voice and tone signaling.

Datasheet: TD450030EN

Product	Part Number	Description
Appliance (complete)	ET-1010-R	Wheelock Vandal Resistant Speaker, Wall/Ceiling-Mount (Surface), Weatherproof, Red, Blank (select WBB backbox as needed)
	ET-1010-W	Wheelock Vandal Resistant Speaker, Wall/Ceiling-Mount (Surface), Weatherproof, White, Blank (select WBB backbox as needed)
Accessory	DBB-R	Backbox, Deep 4 inch square (Steel), Red
	DBB-W	Backbox, Deep 4 inch square (Steel), White
	RP-R	Adapter Plate (Retrofit), Wall-Mount, Red
	RP-W	Adapter Plate (Retrofit), Wall-Mount, White
	SFP-R	Adapter Plate, Semi-Flush, Wall-Mount, Red
	SFP-W	Adapter Plate, Semi-Flush, Wall-Mount, White
	WBB-R	Backbox, Weatherproof, Red
	WBB-R-3/4T-3/4B	Backbox, Weatherproof, 3/4 Threaded, Red
	WBB-W	Backbox, Weatherproof, White
Appliance (complete)	ET-1080-R	Wheelock Vandal Resistant Speaker, Wall/Ceiling-Mount (Flush), Weatherproof, Red, Blank
	ET-1080-W	Wheelock Vandal Resistant Speaker, Wall/Ceiling-Mount (Flush), Weatherproof, White, Blank
Accessory	RP-R	Adapter Plate (Retrofit), Wall-Mount, Red
	RP-W	Adapter Plate (Retrofit), Wall-Mount, White
	SBB-R	Backbox, Wall-Mount (Surface), Red
	SBB-W	Backbox, Wall-Mount (Surface), White
	SFP-R	Adapter Plate, Semi-Flush, Wall-Mount, Red
	SFP-W	Adapter Plate, Semi-Flush, Wall-Mount, White

Other Notification - Speakers and Speakers/Strobes



Wheelock Supervised Self-Amplified Speakers and Speaker/Strobes

The Wheelock SA-S Supervised Self-Amplified Speakers and Speaker Strobes are designed to meet the critical needs for the life safety industry. These speakers and speaker strobes are a perfect fit for SCIF (Sensitive Compartmented Information Facilities) room applications.

Datasheet: TD450047EN

Product	Part Number	Description
Accessory	SBB-R	Backbox, Wall-Mount (Surface), Red
	SBB-W	Backbox, Wall-Mount (Surface), White

Other Notification - Speakers and Speakers/Strobes



Wheelock Vandal Resistant Speakers and Speaker/Strobes

The Wheelock STH cluster speaker with RSS multi-candela strobe is designed for indoor ceiling mounting in high ambient noise environments. It is available with two, three or four speakers for wide area coverage.

Datasheet: TD450078EN

Product	Part Number	Description
Appliance (complete)	STH-15S	Wheelock Horn Loudspeaker, Wall/Ceiling-Mount, 15watts, Gray, Blank
	STH-15SR	Wheelock Horn Loudspeaker, Wall/Ceiling-Mount, 15watts, Red, Blank
	STH-2R24MCCH-FR	Wheelock Cluster Speakers (2) with (1) RSS-24MCCH Strobe, Ceiling-Mount, 115/177cd, Red, "FIRE"
	STH-3R24MCCH-FR	Wheelock Cluster Speakers (3) with (1) RSS-24MCCH Strobe, Ceiling-Mount, 115/177cd, Red, "FIRE"
	STH-4R24MCCH-FR	Wheelock Cluster Speakers (4) with (1) RSS-24MCCH Strobe, Ceiling-Mount, 115/177cd, Red, "FIRE"
	STH-4R24MCCH-NR	Wheelock Cluster Speakers (4) with (1) RSS-24MCCH Strobe, Ceiling-Mount, 115/177cd, Red, Blank
Accessory	SHMP-R	Adapter Plate, Wall/Ceiling-Mount, Red
	SHMP-S	Adapter Plate, Wall/Ceiling-Mount, Gray